Environmental Justice Screening Method:

Integrating Indicators of Cumulative Impact into Regulatory Decision-making



Source: CBE





Rachel Morello-Frosch, UC Berkeley **Manuel Pastor, USC** Jim Sadd, Occidental College

The Primary Research Team







- Manuel Pastor, Ph.D. in Economics, project coordination, statistical analyses, including multivariate and spatial modeling, and popularization
- James Sadd, Ph.D. in Geology, develop and maintain geographic information systems (GIS), including data automation, spatial analysis and geoprocessing
- Rachel Morello-Frosch, Ph.D. in Environmental Health Science statistical analysis, health end-points, and estimates of risk.

Purpose of Screening Methodology

- Develop indicators of cumulative impact that:
 - Reflect research on air pollution, environmental justice, and health
 - Are transparent and relevant to policy-makers and communities
 - Reviewed by community EJ groups, California Air Resources Board (CARB), academic peers and other agencies
- Apply EJ "screening method" to multiple uses:
 - Local land use planning
 - (e.g. Los Angeles, City of Commerce & Richmond – community plans)
 - Regulatory decision-making and enforcement
 - Community outreach



Focus of Screening Method

Specific reference to ambient air quality

Not screening for occupational, indoor, water, pesticides.

Uses secondary databases (<u>screening</u>, not assessment)

 Follows guidance of CARB Air Quality and Land Use Handbook (2005)

Validated by ARB contract Peer Review Committee

 Developed to incorporate land use information into environmental decision-making

Performs best with detailed, high resolution land use data.

First applied in So. California

Completed for Southern California and the Area (16 counties; 76% of population)

In process in 5 southern Central Valley counties.

Screen and map where people are exposed

- Residential land use
- Sensitive land use categories (California ARB land use guidelines, 2005)

Ba



Categories of Impact & Vulnerability








- Proximity to hazards & sensitive land uses
 - Based on EJ literature
 - CARB land use guidelines (sensitive receptors)
 - State data on air quality hazards
- Health risk & exposure
 - Based on EJ and public health literature
 - Available state and national data
 - Modeling from emissions inventories
- Social & health vulnerability
 - Based on epidemiological literature on social determinants of health
 - Based on EJ literature on area-level measures of community vulnerability

Screening Method Architecture






Linking & Mapping

- Step 1: GIS Spatial Assessment
 - Derivation of land use layer
 - Create CI polygon mapping layer (intersects land use polygons with census blocks)
 - Identify land use and hazard proximity metrics for CI polygons
- Step 2: Programming (SPSS)
 - Data processing and cleaning
 - Metrics development
 - Derivation of CI scores
 - By category (Risk, hazard proximity, SES)
 - Total CI score
 - Analytics
 - This work can be done in SAS or R
- Step 3: GIS Mapping of Results
- Essential to Steps 1 3:
 - Quality control of data layers
 - Document and verify metric derivation and scoring
 - Scientific and Community peer review

GIS Spatial Assessment – Derive Land Use Spatial Layer


- 1. Create land use layer by isolating specific land uses
 - "Sensitive land uses" daycare, schools, medical facilities, senior housing, urban parks and playgrounds(CARB, 2005)
 - Residential
- 2. Intersect land use polygons with census blocks
- 3. Resulting Base Map CI Polygons
 - Scoring System each polygon receives "points" related to indicators
 - Final mapping also done using census tracts (discussed later)




Intersect Land Use Polygons with Blocks



Result: Cumulative Impact (CI) Polygons, each associated with a specific block and land use



Each CI Polygon receives a Cumulative Impacts Score



Scoring – Land Use and Hazard Proximity


- Land use polygons receive a score of 1 if they contain at least one sensitive land use category
- Calculate hazard proximity metrics
 - CHAPIS (Priority emitters from California emissions inventories)
 - Chrome Platers
 - Hazardous Waste TSDs
 - Land Uses associated with high levels of air pollution (ARB Handbook)
 - Rail, Ports, Airports, Refineries, Intermodal Distribution Facilities
 - Traffic counts (CARB land use "freeways and high traffic roads")
- Proximity analysis using CI polygons
 - Number of sites within distance of CI polygon boundary
 - Distance-weighted approach to address locational inaccuracy



 Transfer values to census tracts using a populationweighting procedure


Defining Hazard Proximity Distance-weighted Approach

- Buffer CI polygon boundaries <u>at</u> <u>different</u> <u>distances</u>
- Hazard proximity based on number of facilities (pointsources) and hazardous land uses inside the buffer



Defining Proximity – Distance Buffers 2000 Foot Buffer

- Buffer CI polygon boundaries <u>at</u> <u>different</u> <u>distances</u>
- Hazard proximity based on number of facilities (pointsources) and hazardous land uses inside the buffer



Defining Proximity – Distance Buffers *3000 Foot Buffer*

- Buffers on CI polygon boundaries
- Hazard proximity based on number of facilities (pointsources) and hazardous land uses inside the buffer



Distance Weighting the Hazard Count

Because of the potential for inaccurate hazard locations, a distance weighted approach is used to get the hazard count for each CI polygon:

Distance Weighted Hazard Count =

(1 x #Hazards within 1,000ft) +


 $(0.5 \times \text{#Hazards } 1,000-2,000\text{ft}) +$

(**0.1** x #Hazards 2,000-3,000ft)

* The above weights can be set to any desired value

Defining Proximity – Distance Buffers *1000-3000 Foot Buffers, Distance Weighted Hazard Count*

- Buffer CI polygon boundaries at different distances
- Hazard proximity based on number of facilities (pointsources) and hazardous land uses inside the buffer



Next Step: Calculate Hazard Proximity & Sensitive Land Use Counts at the <u>Tract Level</u>

Why?

- Tracts are a consistent level of geography for many sources of data
- All of the health risk and social vulnerability measures (discussed later) are available at the tract level


How Calculated:

- Estimate population in each CI polygon (area-weighting from census blocks)
- Calculate population-weighted average of the hazard and sensitive land use counts using all CI Polygons in each census tract

Scoring: Hazard Proximity & Sensitive Land Use

- Tract-level hazard are ranked into quintiles (1-5) across all tracts in the region to produce the final hazard proximity and sensitive land use <u>score</u>
- Quintile distribution is used throughout the EJ Screening Method because it is an easily understood and normal ranking procedure
 - No "right" distribution to follow (magnitudes of hazards unknown)
 - Other distributions could easily be applied

Hazard Proximity & Sensitive Land Use Score at the Tract Level Mapped on CI Polygons (quintile distribution)



Scoring for Health Risk & Exposure (Tract Level)

Five indicator metrics, all at tract level


- RSEI Toxic conc. hazard scores from TRI facilities (2005)
- NATA Respiratory hazard from mobile/stationary sources (1999)
- CARB Estimated Inhalation Cancer Risk 2001
- CARB estimated PM_{2.5} concentration (2004-06)
- CARB estimated Ozone concentration (2004-06)

Scoring:


- Each indicator is ranked into quintiles (1-5) across all tracts in the region
- Quintile rank values are summed for each tract
- Tract-level sum is ranked into quintiles (1-5) across all tracts in the region
- The resulting quintile rank is the final health risk and exposure score for each tract

Health Risk & Exposure Score at the Tract Level

Mapped on CI Polygons (quintile distribution)




Social & Health Vulnerability Indicators



Social Health & Vulnerability Score at the Tract Level

Mapped on CI Polygons (quintile distribution)



²⁴ Social & Health Vulnerability Scores

- Each social and health vulnerability metric is ranked into quintiles (1-5) across all tracts in the region
- Final score is derived by taking average ranking (across all metrics) for each tract, and ranking the average once again into quintiles (1-5)



A note on missing values:

To help ensure that the social and health vulnerability scores are reliable, we exclude tracts with less than 50 people, and those with 5 or more missing values among the 10 metrics considered. To account for missing values in tracts with 1 to 4 missing metrics, the average quintile ranking is taken across only the non-missing metrics.

Final Cumulative Impact Scores

Combine three categories of impact and vulnerability to derive final Cumulative Impact Score

Cumulative Impact Score =

Hazard Proximity and Sensitive Land Use Score (1-5) +


Health Risk and Exposure Score (1-5) +

Social and Health Vulnerability Score (1-5)

Final Cumulative Impact Score Ranges from 3-15

Tract Level Cumulative Impact Score

Distance weighted hazard proximity, mapped on CI Polygons



Important Caveats

- Method was developed with specific reference to air quality and does not screen for other concerns (such as water quality or pesticides)
 - Performs best with well-classified, high spatial resolution land use data
 - Currently experimenting with other data types to apply the Screening Method more widely



